

Terminal boxes



Description

Model **7012** and **7024 terminal box** is used to connect VW sensors or 4 wire electrical sensors up to 12 sensors or maximum 24 sensors. The sensors in an adjacent area connect signal cables to a terminal box. It provides saving for cost, the reduction of measuring hours and keeping performance of sensors.

These models are composed with terminal block, connector, rotary switch, and case. The case is made of ABS plastic so that it is very strong and waterproof.

Model **7012** can connect the maximum 12ea sensors. If you connect the readout to the terminal box with a cable and then turn the rotary switch, the frequency and temperature will be connected at the same time in the case of a vibrating type sensor, so you can conveniently measure without connecting any cables.

Model **7024** can connect the maximum 24ea sensors, which is useful in large sites or on sites with large amounts of sensor cables.

Specification

Model	7012	7024
Connectional sensors	VW, FSG, mV, mA sensors	
Connectional channel of sensors	Max. 12nos	Max. 24nos
Material	ABS plastic case	
Dimensions	280 × 190 × 180mm	350 × 250 × 180mm
Weight	2kg	3kg

Features

- Possible to semi-automatic
- Waterproof and moisture proof
- Connected up to 12 or 24 VW sensors
- Select consecutively by rotary switch to switch over a frequency and a temperature channels at the same time